NSN 4720-00-881-0033

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-881-0033 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.125 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.437 inches **Minimum Inside Bending Radius:** 8.000 inches Angle Between Rigid Elbow Fittings In Deg: 270.0 **Connection Style:** Swivel nut, flareless 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 2000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

1.625 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

1300.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

47.250 inches working

NSN 4720-00-881-0033

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed	Media	For	Which	Design	ed
--------------------------	-------	-----	-------	--------	----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Specification Data:

96906-ms87029 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0