NSN 4720-00-881-0041



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-881-0041 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.688 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.938 inches **Minimum Inside Bending Radius:** 4.500 inches **Exterior Color:** Natural **Connection Style:** Swivel nut, flareless 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 3750.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:**

Smooth

Measuring Method And Length:

57.625 inches working

NSN 4720-00-881-0041

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ed:
--	-------	-----	-------	--------	-----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 2nd end

Specification Data:

96906-ms87029 government standard

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0