Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-881-0108

Cross Sectional Shape:	
Round	
Thread Class:	
Bb 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.188 inches	
Cempurature Rating:	
65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single resp	ponse
Dutside Diameter:	
0.312 inches	
Connection Style:	
Swivel nut with compression sleeve 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Fhreaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
2000.0 pounds per square inch	
ayer Composition And Location:	
Duter layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
2.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
00.0 degrees 2nd end	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
4.000 inches working	
Thread Series Designator:	
Jnf 2nd end	
Shelf Life:	
√a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0