Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-881-3432

New Online at https://defobdsegfoup.com/hsn/+/20-00-001-5+52	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.375 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
20 1st end	
Burst Test Pressure:	
1700.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided cotton cord and outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
425.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
45.0 degrees 1st end	
Hydrostatic Test Pressure:	
850.0 pounds per square inch	
Outer Covering Environmental Protection:	
Fuel resistant and mildew resistant and oil resistant and ozone resistant and cold resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
20.500 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unf 1st end	

## NSN 4720-00-881-3432

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

