Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-881-8938

ſ	ross Sectional Shape:
	ound
	hread Class:
	o 1st end
-	hread Direction:
	ight-hand 1st end side Diameter:
-	406 inches
	empurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	utside Diameter:
-	562 inches
	inimum Inside Bending Radius:
	625 inches
	onnection Style:
	wivel nut flare 1st end
	nd Connection Design:
	traight 1st end
	onnection Type:
	nreaded internal tube 1st end
	eatures Provided:
El	lectrostatic discharge capability
В	urst Test Pressure:
80	000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
Μ	aximum Operating Pressure:
15	500.0 pounds per square inch
TI	hread Size:
0.	750 inches 1st end
S	eat Angle:
37	7.0 degrees 1st end
H	ydrostatic Test Pressure:
30	000.0 pounds per square inch
Va	acuum In Torr:
50	D.8
In	side Surface Condition:
Sı	mooth
М	easuring Method And Length:
12	2.500 inches working
TI	hread Series Designator:
U	nf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

