## NSN 4720-00-882-1205

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

**Tempurature Rating:** 

**Outside Diameter:** 

0.312 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-882-1205

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Connection Style:						
Swivel nut flare 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Electrostatic discharge capability						
Burst Test Pressure:						
7000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
1500.0 pounds per square inch						
Thread Size:						
0.438 inches 1st end						
Seat Angle:						
37.0 degrees 1st end						
Hydrostatic Test Pressure:						
3000.0 pounds per square inch						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
7.500 inches working						
Special Features:						
In accordance w/aso standard dwg aso-to586						
Thread Series Designator:						
Unf 1st end						
Specification Data:						
81349-mil-h-25579 government specification						

## NSN 4720-00-882-1205

Nonmetallic Hose Assembly - Page 2 of 2



_	_			_	
С.		ficatio	^-	C+	
•	neci	ticatio	n cor	Stanc	ıarn:

4 size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0