NSN 4720-00-882-8291

Cross Sectional Shape:

Round

Thread Class: 2a 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-882-8291

| Tempurature Rating: |
|---|
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.781 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided steel wire and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 2250.0 pounds per square inch |
| Thread Size: |
| 0.375 inches 1st end |
| Seat Angle: |
| 30.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 4500.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Hydraulic solution resistant and mildew resistant and oil resistant and ozone resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 13.000 inches |
| |

NSN 4720-00-882-8291

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unjf 1st end Specification Data: 81349-mil-h-13531 government specification Specification Or Standard: 1 type and a class and 3/8 size Shelf Life: N/a Unit Of Measure: -Demilitarization:

Mil-std (military Standard): Mil-h-13531 spec.

No Fiig: A542a0