Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-882-8296

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.500 inches	
Connection Style:	
Inverted flare 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Thready Qty Per Inch (tpi):	
27 2nd end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided steel wire and outer layer molded rubber	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.250 inches 1st end	
Seat Angle:	
30.0 degrees 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
75.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 2nd end	
Shelf Life:	
N/a	

NSN 4720-00-882-8296

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0