NSN 4720-00-882-9985



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-882-9985 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.560 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Minimum Inside Bending Radius:** 5.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 14 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided wire and outer layer braided wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 65.200 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

NSN 4720-00-882-9985

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0