Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-883-1369

0.000 000000	al Shape:
Round	
Thread Class:	
3b 1st end	
Thread Directi	ion:
Right-hand 1st	end
Inside Diamet	er:
0.219 inches	
Tempurature I	Rating:
-65.0 degrees f	ahrenheit and 158.0 degrees fahrenheit single response
Outside Diame	eter:
0.625 inches	
Connection St	yle:
Swivel nut with	loose or integral clinch sleeve 1st end
End Connection	on Design:
Straight 1st end	t de la constante de
Connection Ty	/pe:
Threaded inter	nal tube 1st end
Features Prov	ided:
Electrostatic di	scharge capability
Thready Qty P	Per Inch (tpi):
20 1st end	
Burst Test Pre	
16000.0 pound	s per square inch
Layer Compos	sition And Location:
1st layer braide	ed corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene	
Maximum Ope	erating Pressure:
-	per square inch
Thread Size:	
0.438 inches 1	st end
Seat Angle:	
12.0 degrees 1	
Hydrostatic Te	
8000.0 pounds	per square inch
Outer Coverin	g Environmental Protection:
	ant and fuel resistant and hydraulic solution resistant and oil resistant and weatherproof
Inside Surface	e Condition:
Smooth	
Media For Wh	ich Designed:
-	Ilic fluid single response
Thread Series	Designator:

NSN 4720-00-883-1369

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

