NSN 4720-00-883-1805

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-883-1805

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.469 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
6000.0 pounds per square inch
The second secon
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Outer layer braided corrosion resistant steel wire
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant

NSN 4720-00-883-1805

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
10.500 inches working
Thread Series Designator:
Unf 2nd end
Specification Data:
81349-mil-h-25579-6 government specification
Specification Or Standard:
1 class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0