## NSN 4720-00-883-2216

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-883-2216

| Round   |
|---|
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.437 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.796 inches  |
| Connection Style:   |
| Swivel nut with compression sleeve 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| End Fitting Component And Material:   |
| Complete fitting steel all ends   |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Thready Qty Per Inch (tpi):   |
| 16 1st end  |
| Second End Relationship With First End:   |
| Identical   |
| Burst Test Pressure:  |
| 14000.0 pounds per square inch  |
| First End Swivel Action Capability:   |
| Included  |
| Layer Composition And Location:   |
| 1st layer braided wire err-100  |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.750 inches 1st end  |
| Seat Angle:   |
| 12.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 21.500 inches working   |
| Special Features:   |
| Inner conveying tube material-rubber, synthetic                                       |

## NSN 4720-00-883-2216

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator | tor: |
|--------------------------|------|
|--------------------------|------|

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0