## NSN 4720-00-883-2230

**Cross Sectional Shape:** 

Round

Un 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-883-2230

Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.875 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
1.313 inches					
Connection Style:					
Swivel nut with compression sleeve 1st end					
End Connection Design:					
Straight 2nd end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
16 1st end					
Burst Test Pressure:					
4500.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and outer layer molded rubber					
Maximum Operating Pressure:					
1125.0 pounds per square inch					
Thread Size:					
1.000 inches 2nd end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
2250.0 pounds per square inch					
Outer Covering Environmental Protection:					
Mildew resistant and oil resistant and oil resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
21.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					
Thread Series Designator:					

## NSN 4720-00-883-2230

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0