

View Online at <https://aerobasegroup.com/nsn/4720-00-883-2234>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.313 inches

Connection Style:

Swivel nut with compression sleeve 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 1st end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber

Maximum Operating Pressure:

1125.0 pounds per square inch

Thread Size:

1.000 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2250.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.880 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0