## NSN 4720-00-883-2234

**Cross Sectional Shape:** 

Round

Un 1st end

Nonmetallic Hose Assembly - Page 1 of 2

**AeroBase** Group

View Online at https://aerobasegroup.com/nsn/4720-00-883-2234

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.313 inches
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber
Maximum Operating Pressure:
1125.0 pounds per square inch
Thread Size:
1.000 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2250.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.880 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

## NSN 4720-00-883-2234

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0