NSN 4720-00-883-3966

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-883-3966

Cross Sectional Shape:					
Round					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.750 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response					
Outside Diameter:					
1.187 inches					
Minimum Inside Bending Radius:					
9.500 inches					
End Application:					
M578 recovery vehicle					
Connection Style:					
Inverted flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded external pipe 1st end					
Burst Test Pressure:					
5000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and outer layer molded rubber					
Maximum Operating Pressure:					
1250.0 pounds per square inch					
Thread Size:					
0.750 inches 1st end					
Seat Angle:					
30.0 degrees 1st end					
Hydrostatic Test Pressure:					
2500.0 pounds per square inch					
Outer Covering Environmental Protection:					
Corrosion resistant and hydraulic solution resistant and oil resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
39.750 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon single response					
Thread Series Designator:					

Nptf 1st end

NSN 4720-00-883-3966

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0