

View Online at <https://aerobasegroup.com/nsn/4720-00-883-9959>

Cross Sectional Shape:

Round

Thread Class:

2b and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.484 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external tube 2nd end

Thready Qty Per Inch (tpi):

24 2nd end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber, synthetic

Thread Size:

0.438 inches 1st end

Seat Angle:

42.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.000 inches and 19.250 inches

Media For Which Designed:

Hydraulic fluid and nonmineral oil single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0