NSN 4720-00-883-9998

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-883-9998

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Angle Between Rigid Elbow Fittings In Deg:
240.0
First End Fitting Specification/std Data:
Mil ms27059 standard (includes industry or association standards, individual manufactureer standards, etc.).
Second End Fitting Specification/std Data:
Mil ms27060 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 2nd end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:

1500.0 pounds per square inch

NSN 4720-00-883-9998

Nonmetallic Hose Assembly - Page 2 of 2



Inread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.600 inches working
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0