## NSN 4720-00-884-4698

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-884-4698 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.531 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fabric and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 300.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 625.0 pounds per square inch **Vacuum In Torr:** 254.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.500 inches Media For Which Designed: Fuel/oil, hydrocarbon and fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

## NSN 4720-00-884-4698

Nonmetallic Hose Assembly - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A542a0