

View Online at <https://aerobasegroup.com/nsn/4720-00-884-6709>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

2.313 inches 2nd end

**Flange Thickness:**

0.380 inches 2nd end

**Outside Diameter:**

1.750 inches

**Minimum Inside Bending Radius:**

11.000 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.000 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

2.000 inches 1st end

**Bolt Hole Quantity:**

3 2nd end

**Flange Length:**

2.500 inches 2nd end

**Flange Width:**

2.625 inches 2nd end

**Connection Style:**

Raised swivel 2nd end

**Bolt Hole Diameter:**

0.340 inches 2nd end

**Raised Face Height:**

0.025 inches 2nd end

**Raised Face Diameter:**

2.330 inches 1st end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

500.0 pounds per square inch

**Hydrostatic Test Pressure:**

1000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

25.125 inches working

**Flange Style:**

Triangular 2nd end

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0