Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-888-2676

| view Online at https://aerobasegroup.com/nsn/4720-00-888-2676 |
|--|
| Cross Sectional Shape: |
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.590 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 4500.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.375 inches 1st end |
| Seat Angle: |
| 30.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant and hydraulic solution resistant and mildew resistant and ozone resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 28.000 inches |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Thread Series Designator: |
| Nptf 1st end |
| Shelf Life: |
| N/a |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13719 spec.