## NSN 4720-00-888-2677

81349-mil-h-13719 government specification

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-888-2677

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.590 inches
Exterior Color:
Black
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant and hydraulic solution resistant and mildew resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.750 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Specification Data:

## NSN 4720-00-888-2677

Nonmetallic Hose Assembly - Page 2 of 2



Specification Or Standard:
1 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-h-13719 spec.