Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-889-6410

~	reas Sectional Shaney
	ross Sectional Shape: ound
-	hread Direction:
	ight-hand 1st end
	nside Diameter:
	etween 0.367 inches and 0.398 inches
	empurature Rating:
	40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
	outside Diameter:
	etween 0.812 inches and 0.875 inches
	linimum Inside Bending Radius:
-	.000 inches
	connection Style:
	nverted flare 1st end
	nd Connection Design:
	traight 1st end
	connection Type:
	hreaded external pipe 1st end
	urst Test Pressure:
	6000.0 pounds per square inch
	ayer Composition And Location:
1	st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic
	laximum Operating Pressure:
4	000.0 pounds per square inch
Т	hread Size:
0	.375 inches 1st end
S	eat Angle:
	0.0 degrees 1st end
	ydrostatic Test Pressure:
	000.0 pounds per square inch
h	nside Surface Condition:
-	mooth
N	leasuring Method And Length:
	2.250 inches
	ledia For Which Designed:
	uel/oil, hydrocarbon single response
Т	hread Series Designator:
	pt 1st end
S	helf Life:
Ν	/a
ι	nit Of Measure:

NSN 4720-00-889-6410

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

