NSN 4720-00-889-8195

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.298 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-889-8195

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.540 inches Minimum Inside Bending Radius: 2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator: Unjf 1st end	Tempurature Rating:
Minimum Inside Bending Radius: 2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Minimum Inside Bending Radius: 2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Outside Diameter:
2.500 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	0.540 inches
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Minimum Inside Bending Radius:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	2.500 inches
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Connection Style:
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Swivel nut flare 1st end
Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	End Connection Design:
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Straight 1st end
Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Connection Type:
Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Threaded internal tube 1st end
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Features Provided:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Electrostatic discharge capability
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Burst Test Pressure:
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	12000.0 pounds per square inch
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Layer Composition And Location:
3000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Outer layer braided corrosion resistant steel wire
Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Maximum Operating Pressure:
O.562 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	3000.0 pounds per square inch
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	0.562 inches 1st end
Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Seat Angle:
6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	37.0 degrees 1st end
Outer Covering Environmental Protection: Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Hydrostatic Test Pressure:
Corrosion resistant Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	6000.0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Outer Covering Environmental Protection:
Smooth Measuring Method And Length: 14.625 inches Thread Series Designator:	Corrosion resistant
Measuring Method And Length: 14.625 inches Thread Series Designator:	Inside Surface Condition:
14.625 inches Thread Series Designator:	Smooth
Thread Series Designator:	Measuring Method And Length:
-	14.625 inches
Unjf 1st end	Thread Series Designator:
	Unjf 1st end

NSN 4720-00-889-8195

Nonmetallic Hose Assembly - Page 2 of 2



Spe	cific	ation	Data:
-----	-------	-------	-------

81349-mil-h-38360 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0