

View Online at <https://aerobasegroup.com/nsn/4720-00-890-2538>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.190 inches

**Temperature Rating:**

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.520 inches

**Minimum Inside Bending Radius:**

0.750 inches

**Exterior Color:**

Black

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

8000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided polyester cord and 2nd layer braided wire and outer layer braided textile yarn

**Maximum Operating Pressure:**

2000.0 pounds per square inch

**Thread Size:**

0.125 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.000 inches

**Media For Which Designed:**

Air and fuel/oil, hydrocarbon and water single response

**Thread Series Designator:**

Nptf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0