NSN 4720-00-890-5296

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-890-5296 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.446 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** Alcohol resistant and alkali resistant and fuel resistant and oil resistant and oxidation resistant and solvent resistant and steam resistant **Vacuum In Torr:**

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

156.000 inches

NSN 4720-00-890-5296

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0