NSN 4720-00-890-6237

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-890-6237
Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
0.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
4.000 inches
Angle Between Rigid Elbow Fittings In Deg:
135.0
Connection Style:
Flared 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded external tube 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

NSN 4720-00-890-6237

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:
-----------	--------	-----	---------

34.625 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0