

View Online at <https://aerobasegroup.com/nsn/4720-00-890-6239>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.406 inches

**Temperature Rating:**

0.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

0.562 inches

**Minimum Inside Bending Radius:**

4.625 inches

**Angle Between Rigid Elbow Fittings In Deg:**

180.0

**Connection Style:**

Flared 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

34.625 inches working

**Special Features:**

Polytetrafluoroethylene external support

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0