## NSN 4720-00-891-4395

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-891-4395

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Outside Diameter:
0.562 inches
Exterior Color:
Black
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 2nd end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
4500.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.688 inches
Media For Which Designed:
Brake fluid, nonmineral oil single response
Thread Series Designator:

Uns 2nd end

## NSN 4720-00-891-4395

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0