## NSN 4720-00-891-5988

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-891-5988 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.344 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 1.500 inches **Minimum Inside Bending Radius:** 9.000 inches **Exterior Color:** Natural **Quick Disconnect Size:** 2.700 inches 2nd end **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Universal quick disconnect 2nd end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 2000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 1.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch **Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

28.625 inches

## NSN 4720-00-891-5988

Nonmetallic Hose Assembly - Page 2 of 2



Err Default:
Err default
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0