Nonmetallic Hose Assembly - Page 1 of 2



Nonmetallic hose Assembly - Lage 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-00-891-5988
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.344 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
Exterior Color:
Natural
Quick Disconnect Size:
2.700 inches 2nd end
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Universal quick disconnect 2nd end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
800.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.625 inches

NSN 4720-00-891-5988

Nonmetallic Hose Assembly - Page 2 of 2

Err Default:

Err default

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

