NSN 4720-00-895-7805

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-895-7805

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
4.000 inches
Angle Between Rigid Elbow Fittings In Deg:
240.0
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
1500.0 pounds per square inch
1500.0 pounds per square inch Thread Size:
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle:
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure:
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle:
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Outer Covering Environmental Protection:
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Outer Covering Environmental Protection: Corrosion resistant
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr:
1500.0 pounds per square inch Thread Size: 1.562 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8

NSN 4720-00-895-7805

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
11.500 inches working
Thread Series Designator:
Unjf 1st end
Specification Data:
99207-3004t75+02 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0