NSN 4720-00-895-9060

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-895-9060

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-60.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Hose Or Tubing Specification/std Data:
Mil mil-h-3992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Mil ms39133 standard (includes industry or association standards, individual manufactureer standards, etc.).
Second End Fitting Specification/std Data:
Ms35746-1 standard (includes industry or association standards, individual manufactureer standards, etc.).
Quick Disconnect Size:
0.375 inches 2nd end
Connection Style:
Plain 1st end
End Connection Design:
Straight 2nd end
Fitting Component And Surface Treatment:
Complete fitting zinc 1st end
Connection Type:
Threaded external pipe 1st end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
900.0 pounds per square inch
First End Swivel Action Capability:
Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Thread Size:

0.500 inches 1st end

External Protection Type And Location (non-core):

Both ends spring guard, round steel coil

Outer Covering Environmental Protection:

Age resistant and mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

NSN 4720-00-895-9060

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
104.000 inches working
Second End Swivel Action Capability:
Not included
Special Features:
External protection type and location- both ends spring guard, round steel coil, inner conveying tube material-rubber, syntheti
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nptf 1st end
Specification Data:
96906-ms39325 government standard
Specification Or Standard:
2 class and 1 type
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):
Mil-h-3992 spec.