

View Online at <https://aerobasegroup.com/nsn/4720-00-895-9060>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-60.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Hose Or Tubing Specification/std Data:

Mil mil-h-3992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil ms39133 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Ms35746-1 standard (includes industry or association standards, individual manufactureer standards, etc.).

Quick Disconnect Size:

0.375 inches 2nd end

Connection Style:

Plain 1st end

End Connection Design:

Straight 2nd end

Fitting Component And Surface Treatment:

Complete fitting zinc 1st end

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Thread Size:

0.500 inches 1st end

External Protection Type And Location (non-core):

Both ends spring guard, round steel coil

Outer Covering Environmental Protection:

Age resistant and mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

104.000 inches working

Second End Swivel Action Capability:

Not included

Special Features:

External protection type and location- both ends spring guard, round steel coil , inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Specification Data:

96906-ms39325 government standard

Specification Or Standard:

2 class and 1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-3992 spec.