

View Online at <https://aerobasegroup.com/nsn/4720-00-896-5217>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.312 inches

Minimum Inside Bending Radius:

2.000 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

9.000 inches working

Thread Series Designator:

Unf 2nd end

Specification Data:

96906-ms8000e government specification

Specification Or Standard:

1 class and 4 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.