Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-899-4798

Cross Se	ctional Shape:
Round	
Thread C	lass:
3b 1st en	t
Thread D	irection:
Right-han	d 1st end
Inside Di	ameter:
0.500 incl	nes
Tempura	ture Rating:
-65.0 deg	rees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside I	Diameter:
0.625 incl	nes
Connecti	on Style:
Swivel nu	t flare 1st end
End Con	nection Design:
Straight 1	st end
Connecti	on Type:
Threaded	internal tube 1st end
Features	Provided:
Electrosta	tic discharge capability
Burst Tes	st Pressure:
7000.0 pc	ounds per square inch
Layer Co	mposition And Location:
Outer laye	er braided corrosion resistant steel wire
Maximun	n Operating Pressure:
1500.0 pc	ounds per square inch
Thread S	ize:
0.875 incl	nes 1st end
Seat Ang	le:
37.0 degr	ees 1st end
Hydrosta	tic Test Pressure:
3000.0 pc	ounds per square inch
Inside Su	Irface Condition:
Smooth	
Measurin	g Method And Length:
5.750 incl	nes working
Thread S	eries Designator:
Unf 1st er	nd
Shelf Life):
N/a	
Unit Of N	leasure:

NSN 4720-00-899-4798

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

