## NSN 4720-00-900-1093

**Cross Sectional Shape:** 

Round

Un 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-900-1093

Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.625 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response				
Outside Diameter:				
0.781 inches				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Electrostatic discharge capability				
Thready Qty Per Inch (tpi):				
12 2nd end				
Burst Test Pressure:				
6000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1000.0 pounds per square inch				
Thread Size:				
1.062 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
2000.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
30.500 inches working				
Thread Series Designator:				

## NSN 4720-00-900-1093

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

73342-6844814-121304 manufacturers source control

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A542a0