Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-900-8661

	nape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.219 inches	
Tempurature Ratin	g:
65.0 degrees fahre	nheit and 200.0 degrees fahrenheit single response
Outside Diameter:	
0.625 inches	
Minimum Inside Be	ending Radius:
3.000 inches	
Connection Style:	
Swivel nut, flareless	s 1st end
End Connection De	esign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Thready Qty Per In	ch (tpi):
20 1st end	
Burst Test Pressur	e:
16000.0 pounds per	square inch
_ayer Compositior	And Location:
st layer braided ste	el wire and 2nd layer braided steel wire and 3rd layer braided cotton cord and outer layer molded rubber
Maximum Operatin	g Pressure:
3000.0 pounds per s	square inch
Thread Size:	
0.438 inches 1st end	t
Seat Angle:	
12.0 degrees 1st en	d
Hydrostatic Test P	ressure:
8000.0 pounds per s	square inch
Outer Covering En	vironmental Protection:
Abrasion resistant a	nd oil resistant
Inside Surface Cor	dition:
Smooth	
Measuring Method	And Length:
58.500 inches work	ing
Media For Which D	esigned:
Eucl/cil bydrocorby	on single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0