Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-901-0746

С	cross Sectional Shape:
R	Cound
т	hread Class:
3	b 1st end
т	hread Direction:
R	light-hand 1st end
Ir	nside Diameter:
0	.312 inches
Т	empurature Rating:
-6	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	Dutside Diameter:
0	.438 inches
N	linimum Inside Bending Radius:
4	.000 inches
С	connection Style:
S	wivel nut with compression sleeve 2nd end
Е	nd Connection Design:
S	traight 1st end
С	connection Type:
Т	hreaded internal tube 1st end
F	eatures Provided:
Е	lectrostatic discharge capability
В	Burst Test Pressure:
9	000.0 pounds per square inch
L	ayer Composition And Location:
0	Outer layer braided corrosion resistant steel wire
Ν	laximum Operating Pressure:
1	500.0 pounds per square inch
т	hread Size:
0	.562 inches 2nd end
S	eat Angle:
1:	2.0 degrees 2nd end
н	lydrostatic Test Pressure:
3	000.0 pounds per square inch
F	low Angle:
9	0.0 degrees 2nd end
v	acuum In Torr:
5	0.8
Ir	nside Surface Condition:
S	mooth
Ν	leasuring Method And Length:
2	5.000 inches working

NSN 4720-00-901-0746

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator: Unf 2nd end Specification Data: 81349-mil-h-25579 government specification Specification Or Standard: 6 size Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fig: A542a0