Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-901-2938

oss Sectional Shape:	
bund	
iread Class:	
1st end	
read Direction:	
ght-hand 1st end	
side Diameter:	
138 inches	
mpurature Rating:	
5.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
utside Diameter:	
359 inches	
nimum Inside Bending Radius:	
750 inches	
onnection Style:	
vivel nut, flareless 1st end	
nd Connection Design:	
raight 1st end	
onnection Type:	
readed internal tube 1st end	
Irst Test Pressure:	
000.0 pounds per square inch	
yer Composition And Location:	
t layer braided steel wire and 2nd layer braided steel wire and 3rd layer braided cotton cord and outer layer molded rul	ber
aximum Operating Pressure:	
00.0 pounds per square inch	
iread Size:	
750 inches 1st end	
eat Angle:	
.0 degrees 1st end	
vdrostatic Test Pressure:	
00.0 pounds per square inch	
Iter Covering Environmental Protection:	
prasion resistant and oil resistant	
side Surface Condition:	
nooth	
easuring Method And Length:	
.625 inches working	
edia For Which Designed:	
el/oil, hydrocarbon single response	
read Series Designator:	
if 1st end	
easuring Method And Length: .625 inches working edia For Which Designed: nel/oil, hydrocarbon single response aread Series Designator:	

Nonmetallic Hose Assembly - Page 2 of 2



**Specification Data:** 

96906-ms28762 government standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0