NSN 4720-00-901-3179

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Outside Diameter:

0.312 inches

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-901-3179

| Angle Between Rigid Elbow Fittings In Deg: | | |
|--|--|--|
| 135.0 | | |
| Connection Style: | | |
| Swivel nut flare 1st end | | |
| End Connection Design: | | |
| Elbow 1st end | | |
| Connection Type: | | |
| Threaded internal tube 1st end | | |
| Features Provided: | | |
| Electrostatic discharge capability | | |
| Burst Test Pressure: | | |
| 12000.0 pounds per square inch | | |
| Layer Composition And Location: | | |
| Outer layer braided corrosion resistant steel wire | | |
| Maximum Operating Pressure: | | |
| 1500.0 pounds per square inch | | |
| Thread Size: | | |
| 0.438 inches 1st end | | |
| Seat Angle: | | |
| 37.0 degrees 1st end | | |
| Hydrostatic Test Pressure: | | |
| 3000.0 pounds per square inch | | |
| Flow Angle: | | |
| 45.0 degrees 1st end | | |
| Outer Covering Environmental Protection: | | |
| Corrosion resistant | | |
| Inside Surface Condition: | | |
| Smooth | | |
| Measuring Method And Length: | | |
| 15.500 inches working | | |
| Thread Series Designator: | | |

NSN 4720-00-901-3179

Nonmetallic Hose Assembly - Page 2 of 2



| Specific | ation | Data: |
|----------|-------|-------|
|----------|-------|-------|

07482-j265b0154b135b manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0