## NSN 4720-00-902-1540

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-902-1540

Cross Sectional Shape:

Cross Sectional Shape:		
Round		
Thread Class:		
2a 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.188 inches		
Tempurature Rating:		
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response		
Outside Diameter:		
0.375 inches		
Connection Style:		
Swivel nut, inverted flare 2nd end		
End Connection Design:		
Straight 2nd end		
Connection Type:		
Threaded external tube 2nd end		
Thready Qty Per Inch (tpi):		
24 2nd end		
Burst Test Pressure:		
2000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided cotton cord and outer layer molded rubber		
Maximum Operating Pressure:		
150.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
45.0 degrees 2nd end		
Hydrostatic Test Pressure:		
1000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Fuel resistant and oil resistant and water resistant		
Vacuum In Torr:		
Vacuum In Torr: 254.0		
254.0		
254.0 Inside Surface Condition:		

\_\_ \_\_ \_\_\_

Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-00-902-1540

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	<b>Designator:</b>

Uns 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0