

View Online at <https://aerobasegroup.com/nsn/4720-00-902-1560>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.380 inches

Temperature Rating:

-65.0 degrees fahrenheit single response

Outside Diameter:

0.840 inches

Minimum Inside Bending Radius:

5.000 inches

Angle Between Rigid Elbow Fittings In Deg:

270.0

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Second End Relationship With First End:

Identical

Burst Test Pressure:

16000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided wire err-100

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Hydraulic solution resistant and fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.500 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0