

View Online at <https://aerobasegroup.com/nsn/4720-00-902-7886>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.219 inches and 0.266 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.469 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

16000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

7.812 inches and 7.875 inches

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0