NSN 4720-00-903-1318

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-903-1318
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Electrostatic discharge capability and perforated outer cover
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
360.000 inches
Special Markings:
2200 psi air
Media For Which Designed:
Air single response
Test Data Document:
81205-29-31648 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Unf 2nd end

Thread Series Designator:

NSN 4720-00-903-1318

Nonmetallic Hose Assembly - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Guided missile remote control system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0