Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-903-3631	
Cross Sectional Sha	ipe:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating	:
-65.0 degrees fahrenh	neit and 250.0 degrees fahrenheit single response
Outside Diameter:	
0.515 inches	
Connection Style:	
Swivel nut flare 1st en	nd
End Connection Des	sign:
Straight 1st end	
Connection Type:	
Threaded internal tube	e 1st end
Burst Test Pressure:	:
12000.0 pounds per s	square inch
Layer Composition A	And Location:
1st layer braided cotto	on cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating	
3000.0 pounds per sq	juare inch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pre	essure:
6000.0 pounds per sq	
Vacuum In Torr:	
50.8	
Inside Surface Cond	lition:
Smooth	
Measuring Method A	And Length:
69.000 inches workin	
Media For Which De	-
Fuel/oil, hydrocarbon	
Thread Series Desig	
Unf 1st end	
Specification Data:	
-	ernment standard

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

