Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-903-4666

Cross	Sectional Shape:
Round	
Threa	d Class:
3b 1st	tend
Threa	d Direction:
Right-	hand 1st end
	e Diameter:
0.188	inches
Temp	urature Rating:
-65.0	degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outsi	de Diameter:
0.312	inches
Minim	num Inside Bending Radius:
2.000	inches
Angle	Between Rigid Elbow Fittings In Deg:
73.0	
Conn	ection Style:
Swive	I nut flare 2nd end
End C	Connection Design:
Elbow	2nd end
Conn	ection Type:
Threa	ded internal tube 1st end
Burst	Test Pressure:
12000	0.0 pounds per square inch
Layer	Composition And Location:
Outer	layer braided corrosion resistant steel wire
Maxir	num Operating Pressure:
1500.	0 pounds per square inch
Threa	d Size:
0.438	inches 1st end
Seat /	Angle:
37.0 c	legrees 2nd end
Hydro	ostatic Test Pressure:
3000.	0 pounds per square inch
Flow	Angle:
90.0 c	legrees 2nd end
Vacu	um In Torr:
50.8	
Inside	e Surface Condition:
Smoo	th
Meas	uring Method And Length:
22.75	3 inches working

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

