Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-903-6653

| | I Shape: |
|----------------------|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Directio | n: |
| Right-hand 1st e | nd |
| Inside Diamete | : |
| 0.875 inches | |
| Tempurature R | ating: |
| -65.0 degrees fa | hrenheit and 200.0 degrees fahrenheit single response |
| Connection Sty | le: |
| Swivel nut with I | pose or integral clinch sleeve 1st end |
| End Connection | ו Design: |
| Straight 1st end | |
| Connection Ty |)e: |
| Threaded internation | al tube 1st end |
| Burst Test Pres | sure: |
| 14000.0 pounds | per square inch |
| Layer Composi | tion And Location: |
| 1st layer braided | steel wire and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Oper | ating Pressure: |
| 3000.0 pounds p | er square inch |
| Thread Size: | |
| 1.312 inches 1st | end |
| Seat Angle: | |
| 12.0 degrees 1s | tend |
| Inside Surface | Condition: |
| Smooth | |
| Measuring Met | nod And Length: |
| 20.625 inches v | <i>r</i> orking |
| Media For Whic | h Designed: |
| Fuel/oil, hydroc | arbon single response |
| Thread Series I | Designator: |
| Unc 1st end | |
| Specification D | ata: |
| 96906-ms28762 | government standard |
| Shelf Life: | |
| N/a | |
| Unit Of Measur | 3: |
| Demilitarizatior | с. |
| No | |

NSN 4720-00-903-6653

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

