

View Online at <https://aerobasegroup.com/nsn/4720-00-904-2328>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.620 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

1.080 inches

Minimum Inside Bending Radius:

6.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

6000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

13.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0