## NSN 4720-00-904-3042

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-904-3042 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.513 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 11000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided synthetic cord and outer layer molded plastic **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5500.0 pounds per square inch **Outer Covering Environmental Protection:** Hydraulic solution resistant and ozone resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:** 57.000 inches working **Thread Series Designator:** Unf 1st end

Unf 1st end
Shelf Life:

N/a

## NSN 4720-00-904-3042

Nonmetallic Hose Assembly - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0